

## INSTALLING FILTER ASSEMBLY- 600 D, DX

The AllerAir 600 models ship with their large carbon filters in a separate box. This is done to safeguard your unit during shipping. To insert the filter, refer to the diagram below.

Step 2

Step 5

With a #2 Philips screw driver,

bottom of the unit.

remove the four screws from the




Step 1 Turn Power Off and unplug receptacle. Lay unit upside down.



Step 4 Remove only one of the white, felt, donut-shaped gaskets from the inside of the purifier body.



Step 7 Place lid back to its proper position by aligning the arrow with the rear seam.



Insert the carbon filter (either a

DX Carbon) into the unit.

Model 600 D Carbon or a Model 600

Step 8 Replace the four screws



0

Allergi

Turn the unit back onto its wheels.

It is now ready for immediate use.

Step 3

the wheels.

Gently grasp wheels.

Remove base by gently pulling on



**INSTALLING FILTER ASSEMBLY- 600 Models** (except D and DX)

The AllerAir 600 models ship with their large carbon filters in a separate box.

This is done to safeguard your unit during shipping. To insert the filter, refer to the diagram below.



Allerhir



Step 2 With a #2 Philips screw driver, remove the four screws from the



Step 3 Gently grasp wheels.







bottom of the unit.

Step 5 First remove the HEPA filter by placing thumbs on the inner side of the filter. Then pull up gently until totally out.



Step 6 Than remove the **Carbon filter** by placing thumbs on the inner side of the filter. Then pull up gently until totally out.




## Step 7

Replace filters with new ones then reassemble by inserting the Carbon filter first then the HEPA filter.



Step 8 Place lid back to its proper position by aligning the arrow with the rear seam.



Step 9 With a screw driver, place 4 screws back into their positions. Gently return the unit into upright position.

AllerAir Industries Inc. Toll free: 1-888-852-8247 / Fax: 1-877-688-3939 www.allerair.com

Step 9



## INSTALLING FILTER ASSEMBLY- 600 D, DX

The AllerAir 600 models ship with their large carbon filters in a separate box. This is done to safeguard your unit during shipping. To insert the filter, refer to the diagram below.

Step 2

Step 5

With a #2 Philips screw driver,

bottom of the unit.

remove the four screws from the




Step 1 Turn Power Off and unplug receptacle. Lay unit upside down.



Step 4 Remove only one of the white, felt, donut-shaped gaskets from the inside of the purifier body.



Step 7 Place lid back to its proper position by aligning the arrow with the rear seam.



Insert the carbon filter (either a

DX Carbon) into the unit.

Model 600 D Carbon or a Model 600

Step 8 Replace the four screws



0

Allergi

Turn the unit back onto its wheels.

It is now ready for immediate use.

Step 3

the wheels.

Gently grasp wheels.

Remove base by gently pulling on



**INSTALLING FILTER ASSEMBLY- 600 Models** (except D and DX)

The AllerAir 600 models ship with their large carbon filters in a separate box.

This is done to safeguard your unit during shipping. To insert the filter, refer to the diagram below.



Allerhir



Step 2 With a #2 Philips screw driver, remove the four screws from the



Step 3 Gently grasp wheels.







bottom of the unit.

Step 5 First remove the HEPA filter by placing thumbs on the inner side of the filter. Then pull up gently until totally out.



Step 6 Than remove the **Carbon filter** by placing thumbs on the inner side of the filter. Then pull up gently until totally out.




## Step 7

Replace filters with new ones then reassemble by inserting the Carbon filter first then the HEPA filter.



Step 8 Place lid back to its proper position by aligning the arrow with the rear seam.



Step 9 With a screw driver, place 4 screws back into their positions. Gently return the unit into upright position.

AllerAir Industries Inc. Toll free: 1-888-852-8247 / Fax: 1-877-688-3939 www.allerair.com

Step 9